

# HAND PROTECTION

## ARAX HEAVY DUTY GLOVES

PRODUCT DATA SHEET: AFND-(SIZE)

**PRO**  
PRO CHOICE SAFETY GEAR

PRODUCT CODE:  
AFND-(SIZE)



### FEATURES AND BENEFITS

- EN388:2016 Cut Resistance Level "D"
- Contact heat resistant to 100°C
- Good cut resistance without sacrificing comfort or dexterity
- Dual layer palm - nitrile foam and chrome leather for heavy duty applications
- Breathable Arax® liner
- Form fitting for comfortable all day wear
- Colour coded cuff for size identification

### APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut and Abrasion Risks.

### PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	8.5cm +/-	22.5cm +/-
8	9.5cm +/-	23.0cm +/-
9	10.0cm +/-	25.5cm +/-
10	10.5cm +/-	26.0cm +/-
11	10.5cm +/-	28.5cm +/-

### AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
AFND-(SIZE)	12 pairs	120 pairs

### CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200g
B	≥5	500g
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

### PRODUCT DETAILS

**Material:** Engineered Composite 13 Gauge Seamless Arax® Liner  
**Dip:** Nitrile Foam in Black  
**Palm:** Chrome Leather Reinforced  
**Cuff Type:** Knitted  
**Colour:** Blue Speckle  
**Sizes:** 7, 8, 9, 10, 11

### STANDARDS

#### CE CATEGORY:

II Intermediary risks in accordance with:

EN420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2016 Protection Against Mechanical Risks  
**Results:** 4X44D

EN407 AS/NZS 2161.4:1999 Protection Against Thermal Risks  
 (Heat and Fire)

**Results:** X1XXXX

ASTM F1 790 Cut Level

**Results:** 4

