

PROBELL™ DISPOSABLE EAR PLUGS | CORDED & UNCORDED

PRODUCT CODE: EPYU | EPYC



EPYU



EPYC

FEATURES

- Hearing protection for noise levels to 112dB(A)
- Hi-vis yellow for visual identification and compliance
- Economical and convenient choice for work situations that demand a high degree of comfort, frequent changes or where hygiene presents a problem for re-usage
- Bell shape provides maximum comfort
- Design makes it easier to insert and reduces tendency to back out of the ear
- Pairs packaged in individual poly bags
- Refill bag compatible with the Pro Choice Safety Gear ear plug dispenser station

SPECIFICATIONS

Material: PU Foam

Length: 2.5cm

Diameter: 1.6cm

Colour: Hi-Vis Yellow Foam, Blue Cord

APPLICATIONS

- Agriculture
- Aviation
- Automotive
- Chemical Manufacturing
- Construction
- Forestry
- Heavy Engineering
- Metal processing
- Mining and Quarrying
- Welding
- Woodworking

PACKAGING

EPYU (Uncorded)

Unit: 1 Pair/Bag | **Pack:** 200 Pairs/Box | **Carton:** 10 Boxes

EPYC (Corded)

Unit: 1 Pair/Bag | **Pack:** 100 Pairs/Box | **Carton:** 10 Boxes

CARE INSTRUCTIONS

These ear plugs are disposable, but when not in use should be kept in clean, dry conditions.

TEST DATA

ATTENUATION TABLE (IN DECIBELS)

FREQUENCY HZ	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION	22.9	25.5	29.8	30.0	32.4	40.1	40.1
STANDARD DEVIATION	6.5	6.3	7.0	6.8	4.9	6.6	7.0
MEAN-MINUS-STANDARD DEVIATION ATTENUATIONS	16.4	19.2	22.8	23.2	27.5	33.5	33.1

SLC₈₀ Value is 26 (Class 5)

STANDARDS

AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 26dB

When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 112dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.

