

PROTECTIVE HEADWEAR

V9 VENTED HARD HAT

PRODUCT DATA SHEET: HHV9-(COLOUR)

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
HHV9-W



FEATURES AND BENEFITS

HELMET

- Certified to AS/NZS 1801:1997 Type 1 Industrial Occupational Protective Helmets.
- Complete with 9 ventilation points.
- Lightweight ABS plastic vented hard hat.
- Extended peak & rain gutter to assist with sun shade & help protect wearer from rain.
- Replaceable cotton sweatband.
- 25mm moulded earmuff slots to accommodate Pro Choice Safety Gear hearing protection.

HARNESSES

- Fits all head sizes: 53cm - 66cm.
- 6 point 25mm webbing harness.
- Pro Choice Safety Gear PushLock harness adjustment.
- Functional sizing harness to improve fit & comfort.
- Replacement harness code: HHHPL-V9.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
HHV9-(COLOUR)	EACH	1	20

White (HHV9-W), Fluoro Orange (HHV9-FO), Fluoro Pink (HHV9-FP), Fluoro Yellow (HHV9-FY), Blue (HHV9-B), Green (HHV9-G), Orange (HHV9-O), Red (HHV9-R), Yellow (HHV9-Y), Black (HHV9-BK), Grey (HHV9-GY).

APPLICATIONS

The Pro Choice Safety Gear range of range hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to:

Agriculture, Aviation, Automotive, Chemical manufacturing, Construction, Heavy engineering, Metal processing, Mining and Quarrying, Welding, Woodworking.

PRODUCT DETAILS

Helmet Material:	ABS Plastic
Harness Materials:	HDPE/Polyester
Weight:	362g ± 2
Colours:	White, Fluoro Orange, Fluoro Pink, Fluoro Yellow, Blue, Green, Orange, Red, Yellow, Black, Grey
Size:	53cm - 66cm



ADJUSTABLE



BREATHABLE



LIGHTWEIGHT



LOGO PRINTING



MODULAR



OSFA

CARE INSTRUCTIONS

Upon issue, wearers name & date of issue should be printed on the label provided.

Pro Choice Safety Gear hard hats should be inspected for any deterioration or damage prior to use. Pro Choice Safety Gear hard hats with excessive damage (cracks, colour distortion or deep abrasions) should be disposed of. Entire hard hat, including harness, should be cleaned with warm soapy water (avoid any solvents) on a regular basis & sweatband replaced.

Industry recommends hard hat shell be replaced after 3 years of working life.

Components of the hard hat harness may deteriorate during its normal working life, & as a result the harness should be replaced at intervals no longer than 2 years.

To extend your hard hat working life, avoid excessive exposure to UV & any solvents.

HARD HAT PRINTING SERVICE

The need to distinguish workers in various occupations on a work site can be for safety or convenience.

For example, having a safety officer readily identified by the colour of their hard hat can improve efficiencies; while being aware of who is a visitor or sub-contractor can improve security.

To further enhance these advantages, Pro Choice Safety Gear now offers a pad printing & a vinyl printing service that can customise hard hats - before a customer takes delivery.

Speak to your Pro Choice Safety Gear sales representative about adding value to your hard hat sales by utilising our pad printing or vinyl cut print service.

STANDARDS

CERTIFIED TO:

AS/NZS 1801:1997 Type 1 Industrial Occupational Protective Helmets

To be used in conjunction with:

AS/NZS 1800:1998 Occupational Protective Helmets - Selection, care & use



AS/NZS1801:1997
Lic 20500

PROCHOICE SAFETY GEAR AUSTRALIA
2/980 ABERNETHY ROAD,
HIGH WYCOMBE, WA 6057
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PROCHOICE SAFETY GEAR NEW ZEALAND
7 SIR WOLFF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PIPANZ.COM

PRO
PRO CHOICE SAFETY GEAR
BY PIP