

HAND PROTECTION

ARAX HEAVY DUTY GLOVES

PRODUCT CODE: AFND-(SIZE)

PRO
PRO CHOICE SAFETY GEAR



FEATURES

- EN388:2016 Cut Resistance Level "D"
- Contact heat resistant to 100°C
- Good cut resistance without sacrificing comfort or dexterity
- Dual layer palm - nitrile foam and chrome leather for heavy duty applications
- Breathable Arax® liner
- Form fitting for comfortable all day wear
- Colour coded cuff for size identification

SPECIFICATIONS

Material: Engineered Composite 13 Gauge Seamless Arax® Liner
Dip: Nitrile Foam in Black
Palm: Chrome Leather Reinforced
Cuff Type: Knitted
Colour: Blue Speckle
Sizes: 7, 8, 9, 10, 11

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

| PERFORMANCE LEVEL | NEWTON | WEIGHT |
|-------------------|------------|--------------|
| A | <2 | 200g |
| B | ≥5 | 500g |
| C | ≥10 | 1kg |
| D | ≥15 | 1.5kg |
| E | ≥22 | 2.2kg |
| F | ≥30 | 3.0kg |

PHYSICAL DIMENSIONS

| SIZE | PALM WIDTH | GLOVE LENGTH |
|------|------------|--------------|
| 7 | 8.5cm +/- | 22.5cm +/- |
| 8 | 9.5cm +/- | 23.0cm +/- |
| 9 | 10.0cm +/- | 25.5cm +/- |
| 10 | 10.5cm +/- | 26.0cm +/- |
| 11 | 10.5cm +/- | 28.5cm +/- |

APPLICATIONS

- Metal Fabrication
- Sheet Metal Handling
- Glass/Tiles/Ceramic Handling
- Rigging
- Landscaping
- Construction
- Mining
- Materials Handling
- Demolition
- Cut and Abrasion Risks

PACKAGING

Unit: 1 pair | Inner: 12 pairs | Carton: 120 pairs

STANDARDS



AS/NZS 2161.3:2005
BMP NO. 668611

CAT. II